

Welding Supplies

REGINA
(306) 525-2551

YORKTON
(306) 783-6515

ESTEVAN
(306) 634-3664

WEYBURN
(306) 842-4676

MAINLINE FLEET
(306) 721-7711

EMERALD PARK
(306) 993-1629

SILVER HEAVY-DUTY WELDING & CUTTING OUTFITS

- Can weld up to 1/2" and cut up to 3/4"
- Ideal for industrial and commercial applications
- Victor® Cutskill® compatible



Includes:

- Torch handle with check valve
- Cutting attachment
- Oxygen/acetylene regulators with 2 1/2" double-scale gauges
- Cutting tip #1
- Welding nozzle #2
- T-Grade 17.5' twin hose
- Goggles
- Striker

TTV022

REGINA

YORKTON

ESTEVAN

WEYBURN

EMERALD PARK



**AUTOMOTIVE PARTS
AUTO BODY SUPPLY**

**TOOLS & EQUIPMENT
INDUSTRIAL & SAFETY SUPPLY**

WELDING HELMET

- Lightweight design with ratchet headgear
- Comes complete with shade 10 lens
- Passive lens
- Material: Thermoplastic
- Meets ANSI/ISEA Z87.1-2015



NT687

DYNAMIC™ WHISTLER™ HARDHAT

- Lightweight high density polyethylene
- Attachment points for chin straps
- 4-point ratchet suspension
- Accommodates accessories
 - Hearing protection
 - Welding protection
 - Face shields



SFY730

TIG WELDER GLOVES

Part # Size

- Goatskin grain, unlined
- Abrasion-resistant
- Thumb strap for durability
- Gauntlet cuff

NJC611 Size 10

NJC612 Size 11



NJC611
NJC612

- Split deerskin
- Unlined
- Straight thumb, double thumb strap
- 4" gauntlet cuff
- Sewn with DuPont® Kevlar® thread for higher seam strength and seam flame resistance

SM599 Large

SM600 X-Large



SM599
SM600

NITRILE GLOVES

- Flock-lined, embossed finish
- 17-mil thickness
- Straight-cuff
- 13" length

Part # Size

SAW944 9 / Large

SAW945 10 / X-Large



SAW944
SAW945

OUTSIDE LENSES FOR WELDING HELMETS

Part # Size Shade

POLYCARBONATE COVER LENSES

NT601 2" x 4-1/4" Clear

NT602 4-1/2" x 5-1/4" Clear

GLASS COVER LENSES

Clear glass lenses are **not** impact-resistant, and are only for use against spatter.

SAN058 2" x 4-1/4" Clear

SAN059 4-1/2" x 5-1/4" Clear

HARDENED GLASS FILTER PLATE LENSES

SAN065 2" x 4-1/4" 8

SAN066 2" x 4-1/4" 9

SAN076 4-1/2" x 5-1/4" 8

SAN077 4-1/2" x 5-1/4" 9

NT602



SAN059



SAN076
SAN077



NT601



SAN058



SAN065
SAN066



REGINA

• YORKTON

• ESTEVAN

• WEYBURN

• EMERALD PARK



**AUTOMOTIVE PARTS
AUTO BODY SUPPLY**

**TOOLS & EQUIPMENT
INDUSTRIAL & SAFETY SUPPLY**

WELD-KLEEN HD ANTI-SPATTER

- 20oz Aerosol
- Paintable
- Non-flammable
- Protects parts, tooling, and fixtures

388-1165



MIG WIRE CLEANING PADS

- Pack of 6
- Designed for use on all MIG wire feeders
- Removes dust and dirt from WIRE
- Treated pads can be used on all alloyed wires except aluminum



720-1000KIT

NOZZLE GEL



- For MIG gun nozzles and contact tips
- Non toxic, odourless
- Not flammable, silicone free
- 16 oz.

720-1071

“TOOTHBRUSH” INDUSTRIAL-DUTY SCRATCH BRUSH

- Brush length: 1-1/2"
- Overall length: 7-3/4"
- Stainless steel wire bristles
- 1/2" trim length
- 3x7 rows



NT615

LUBE PADS

- Clean and lubricate wire, improve feedability, reduce spatter and increase tip and liner life
- Reduces wire drag by 60% and feeds wire more smoothly with poor cast, helix and rust
- Black lube pads are pre-treated with Lube-Matic® liquid
- Fluid bottle not included, 6 pads per pack

388-1010



FLINTS & LIGHTERS


Part # Description

FLINTS

TTU072	Individual tri-flints
NT663	5 Flints with Holder

LIGHTERS

NT642	Single-flint striker
TTU071	Three-flint lighter



TTU072



NT642



NT663



TTU071

CAM ACTION CABLE CONNECTORS

- Male/female connector set
- For use with single flint lighter NT663 and other Weld-Mate single flint lighters
- One model fits cable sizes 4 through 4/0

NT664



REGINA

YORKTON

ESTEVAN

WEYBURN

EMERALD PARK



AUTOMOTIVE PARTS
AUTO BODY SUPPLY

TOOLS & EQUIPMENT
INDUSTRIAL & SAFETY SUPPLY

GROUND CLAMPS

- 500 amperage rating

AUW394



HEAVY-DUTY GROUND CLAMPS

- Includes allen wrench
- Heavy-duty spring

NT669



8" MIG PLIERS

NP537



CHIPPING HAMMER

- 10 1/2" overall length
- Cone and chisel head
- 6 1/4" head length
- Solid steel handle

NP532



WHITE SOAPSTONES

- 5" (L) x 1/2" (W) x 3/16" (H)

NT225



FLAT SOAPSTONE HOLDER

- Steel adjustable holder for 1/2" x 5" flat soapstone or chalk
- Comes with one installed soapstone

NT639



FLASHBACK ARRESTORS

Part #

Description

312-3376

Torch Style

312-3377

Regulator Adaptor Style



QUICK-CONNECT

- Regulator-to-Hose w/Check Valves
- Brass construction provides long service life - cycle tested over 10 000 operations indicating a service life of 10 to 12 years of comparable use

312-4284



ARGON REGULATORS

Part #

Series

Description

FLOW GAUGE REGULATORS

331-1540

190

- Max Inlet: 0-50 PSI
- Inlet gauge: 2", 4000 PSI
- Outlet gauge: 2", 50 SCFH

FLOW METER REGULATORS

331-1610

191

- Flow capacity: 50 SCFH
- Flowmeter: 60 SCFH
- Inlet gauge: 1.5", 4000 PSI

331-4150

191

- Same as 331-1610, includes 6' hose

ACCESSORIES

331-2595

- Hood flow meter



REGINA

YORKTON

ESTEVAN

WEYBURN

EMERALD PARK



**AUTOMOTIVE PARTS
AUTO BODY SUPPLY**

**TOOLS & EQUIPMENT
INDUSTRIAL & SAFETY SUPPLY**

E71TGS SELF-SHIELDING MID STEEL FLUX-CORED WELDING WIRE

- Self-shielding-Welds steel without gas
- Gasless steel welding wire for single pass applications
- Excellent for use on thin gauges of galvanised and mild steels

Part # Description

SPOOL WEIGHT: 2 lbs

- | | |
|--------|-------------------------|
| TTU700 | • Wire diameter: 0.030" |
| TTU701 | • Wire diameter: 0.035" |

SPOOL WEIGHT: 10 lbs

- | | |
|--------|-------------------------|
| TTU702 | • Wire diameter: 0.030" |
| TTU703 | • Wire diameter: 0.035" |

SPOOL WEIGHT: 25 lbs

- | | |
|--------|-------------------------|
| TTU706 | • Wire diameter: 0.045" |
|--------|-------------------------|



E71TGS

ER70S6 CARBON STEEL WELDING WIRE

- Highest combination of manganese and silicone deoxidizers
- Permits high current welding with CO2 gas shielding
- Can also be applied with ArCO2
- Excellent wetting
- Layer/level wound wire
- Certified by CWB to CSA class W48 for ER49S-6
- Certified by AWS to class A5.18 for ER70S6

Part # Description

Spool Weight: 2 lbs / 0.9 kg

- | | |
|-------|-------------------------|
| NT550 | • Wire diameter: 0.030" |
| NT551 | • Wire diameter: 0.035" |
| NT552 | • Wire diameter: 0.045" |

Spool Weight: 11 lbs / 5 kg

- | | |
|-------|-------------------------|
| NT554 | • Wire diameter: 0.030" |
| NT555 | • Wire diameter: 0.035" |

Spool Weight: 33 lbs / 15 kg

- | | |
|-------|-------------------------|
| NT557 | • Wire diameter: 0.030" |
|-------|-------------------------|

Spool Weight: 44 lbs / 20 kg

- | | |
|-------|-------------------------|
| NT560 | • Wire diameter: 0.035" |
| NT561 | • Wire diameter: 0.045" |



ER70S6

4043 ALUMINUM WELDING WIRE

- Cleanliness, density and temper of wires precisely controlled
- Each container has an identification label showing grade, size, weight and heat number
- Conform to AWS A5.10 classification, CWB and ABS approvals
- 5% silicon all position aluminum weld wire used to weld heat treatable alloys such as the 6XXX base metals and cast alloys
- Found in many common welding applications such as bicycles, trucks, trailers and automotive parts and equipment
- Silicon with these alloys give improved wetting action yielding a less crack sensitive bright weld bead
- Diameter: 0.035"
- Sold as a spool



TTU957

REGINA

YORKTON

ESTEVAN

WEYBURN

EMERALD PARK



**AUTOMOTIVE PARTS
AUTO BODY SUPPLY**

**TOOLS & EQUIPMENT
INDUSTRIAL & SAFETY SUPPLY**

ELECTRODES & HOLDERS

Part # Description

ELECTRODES

909-2740 PT176655 Hafnium Electrode

TTU095 Thermal Dynamic Electrode

MILD STEEL STICK ELECTRODES (5lb tubes)

6010 Series

- High cellulose coated
- Produce a flat weld bead with coarse ripples and a thin easily removable slag
- May be used in the flat, horizontal, vertical or overhead welding positions

TTU708 • 1/8" diameter

6011 Series

- A versatile, deep penetrating, all-position electrode for steel
- Excellent mechanical properties in welding of mild steels, galvanised & some low alloy steels
- Operate on AC or DCEP

TTU710 • 3/32" diameter

TTU711 • 1/8" diameter

TTU712 • 5/32" diameter

6013 Series

- A general purpose, all-position electrodes for mild steel
- Slag lifts easily, revealing a finely rippled bead contour
- Ideally suited for general purpose welding, even with small AC power sources having low open-circuit voltage
- Operates on AC, DCEN or DCEP

TTU714 • 1/8" diameter

7014 Series

- An all position electrode for mild and low alloy steels
- Iron powder covering content yields a high deposition rate in all positions
- Particularly advantageous when poor fit-up exists
- Operates on AC, DCEN or DCEP

TTU716 • 3/32" diameter

TTU717 • 1/8" diameter

TTU718 • 5/32" diameter

7018 Series

- A high deposition electrode for low and medium carbon steels
- An efficient, all-position, iron powder, low hydrogen type electrode
- Exhibits excellent mechanical properties, crack resistant and X-ray quality welds
- Operates on AC or DCEP

TTU719 • 3/32" diameter

TTU720 • 1/8" diameter

TTU721 • 5/32" diameter

ELECTRODE HOLDERS

- Amperage rating: 400

360-9001 Bernard® Shortstub™ Electrode Holder

- 2000lb gripping pressure
- Electrode capacity: 1/16" - 1/4"
- Can be used within one inch of ShortStub™ head

NT629 Electrode Holder with Neck Ring

- Electrode capacity: 3/32" - 3/16"

NT630 Slimline - Bernard® Style Holder

- Electrode capacity: 3/32" - 3/16"

TTU095



909-2740



NT629

All Mild Steel Stick Electrodes



NT630



360-9001

REGINA

• YORKTON

• ESTEVAN

• WEYBURN

• EMERALD PARK



**AUTOMOTIVE PARTS
AUTO BODY SUPPLY**

**TOOLS & EQUIPMENT
INDUSTRIAL & SAFETY SUPPLY**

MIG GUN ACCESSORIES

Part # Description

GAS DIFFUSERS

- 379-1570 • Standard, 160 amps

Tweco® Style

- 379-1635 • For fixed nozzle, 200 amps

- NT191 • Standard, 300 / 400 amps

15' LINER ASSEMBLIES

Tweco® Style

- 379-1600 • 200 amps, 0.040" - 0.045"

- TTT239 • 160 amps, 0.045"

Miller® Style

- TTT189 • 150 / 250 amps, 0.030" - 0.035"

- TTT190 • 150 / 250 amps, 0.035" - 0.045"



379-1570



379-1635



NT191



379-1600



TTT239



TTT189
TTT190

3M POLYESTER TAPE

- 24mm x 22m [1" x 72']
- Works in temperatures ranging from -6°F [-5°C] to 4°F [24°C]
- Colour: Green

AG772



GENERAL-PURPOSE PASTE SOLDERING FLUX

- Not recommended for electrical/electronic applications
- Effective to 700°F
- Meets Fed. Spec. O-F 506C, Type 1, Form A, & MIL-S-6872A
- 4 oz jar

TTU918



SOLDER

- Wire Diameter: 1/16"
- Core Type: Rosin
- Composition: 60% Tin, 40% Lead
- Lead-based

TTV814



36" CUT LENGTH TIG RODS

- Diameter: 1/8"
- Low fuming Bronze-flux coated

TTU946



MIG/TIG INERT GAS HOSE

- Inside diameter: 1/4"
- Hose length: 6'

TTU563



REGINA

• YORKTON

• ESTEVAN

• WEYBURN

• EMERALD PARK



**AUTOMOTIVE PARTS
AUTO BODY SUPPLY**

**TOOLS & EQUIPMENT
INDUSTRIAL & SAFETY SUPPLY**

AIRCO® STYLE CUTTING TIPS

Part # Description

ACETYLENE-OXYGEN CUTTING TIPS

- Fits Airco 3790, 4690, 4700, 4800, 5700, 5800, 1100, 3000, 9000 and 9500

TTU358

- Style: 164/ALC 803
- Size: 0
- For general cutting, cutting cast iron and stainless steel
- Very heavy preheat

TTU467

- Style: 144/ALC 802
- Size: 1
- For general hand or machine cutting
- Medium preheat



MILLER® STYLE

Part # Description

5/8" NOZZLES - 5/8", 250 amps

379-1050

- Flush

TTT177

- 1/8" Tip stickout

NOZZLE RETAINERS

379-1055

- Nozzle Retainer
- 250 amps

TTT180

- Retaining Head
- 150 amps

SHOCK WASHERS

TTT184

- 250 amps



VICTOR® STYLE TIPS

Part # Description

Size

ACETYLENE-OXYGEN CUTTING TIPS

- Machine preheat for hand and machine cutting
- Fits 2460, CA 1060, ST, SST and 1400C machine torches

TTU334 • Style 1-101 0

TTU335 • Style 1-101 1

TTU337 • Style 1-101 3

- Medium preheat
- Fits CA 1260, CA 1350, C 1450, CA 2060, CST 800 and C 1400 torches

TTU340 • Style 3-101 0

TTU341 • Style 3-101 1

TTU343 • Style 3-101 3

- Medium preheat
- For general hand-cutting, one-piece

TTV361 • Style 3-101 1

PROPANE / OXYGEN-NATURAL GAS CUTTING TIPS


- Medium preheat for hand and machine cutting
- Fits 2450, CA 1060, CAN 1060, ST, SST, STN and 1400C machine torches

TTU346 • GPN Style 2

- Medium preheat series 3 tip
- Fits CA 1260, CA 1350, C 1450, CA 2060, CST 800 and C 1400 torches

TTU455 • 3-GPN Style 1

TTU456 • 3-GPN Style 2



REGINA

YORKTON

ESTEVAN

WEYBURN

EMERALD PARK



**AUTOMOTIVE PARTS
AUTO BODY SUPPLY**

**TOOLS & EQUIPMENT
INDUSTRIAL & SAFETY SUPPLY**

BERNARD® STYLE WELDING NOZZLE

- Brass
- 5/8" I.D.
- Amperage: 200, 300



NT177

BERNARD® STYLE ELLIPTICAL NOZZLE

- Brass Nozzle Head Assembly
- Wire Size: 5/8"

360-3015



WELDING TIPS

Part #	Description
331-1367	Heating Nozzle Tip <ul style="list-style-type: none"> • Tip Size: 0
NP666	MIG Welding Tip <ul style="list-style-type: none"> • Tip Size: 0.023"
TTT193	MIG Welding Tip <ul style="list-style-type: none"> • Contact Tip-Tapered • Tip size: 0.023"



SPIRAL TIP CLEANER

- Includes 12 cleaners and hardened steel file
- Cleaning data on back of case

NT641



TWECO® STYLE TIPS & NOZZLES

Part #	Description
NOZZLES	
379-1455	<ul style="list-style-type: none"> • Standard • 1/2" I.D.
NP617	<ul style="list-style-type: none"> • Self-insulated • 1/2" I.D. • 200 / 300 / 400 amps
NP622	<ul style="list-style-type: none"> • Adjustable, Standard • 5/8 I.D. • 300 / 400 amps
NP628	Nozzle Insulator <ul style="list-style-type: none"> • Standard • 300 / 400 amps
CONTACT TIPS	
NP602	<ul style="list-style-type: none"> • 0.023" • 200 amps
NP603	<ul style="list-style-type: none"> • 0.030" • 200 / 300 amps
<ul style="list-style-type: none"> • Heavy-duty • 200 / 300 / 400 amps 	
NP611	<ul style="list-style-type: none"> • 0.035"
NP613	<ul style="list-style-type: none"> • 0.045"
<ul style="list-style-type: none"> • 150 / 250 amps • For use with Miller® style 	
NT165	<ul style="list-style-type: none"> • 0.030"
NT166	<ul style="list-style-type: none"> • 0.035"
NT167	<ul style="list-style-type: none"> • 0.045"
<ul style="list-style-type: none"> • 160 Amps CO2 @ 80% duty cycle • 100 Amps mixed gas @ 80% duty cycle 	
379-1265	<ul style="list-style-type: none"> • 0.023"
379-1270	<ul style="list-style-type: none"> • 0.030"
379-1275	<ul style="list-style-type: none"> • 0.035", Standard



REGINA

YORKTON

ESTEVAN

WEYBURN

EMERALD PARK



**AUTOMOTIVE PARTS
AUTO BODY SUPPLY**

**TOOLS & EQUIPMENT
INDUSTRIAL & SAFETY SUPPLY**



AUTO 
electric service
SALES • PARTS • SERVICE


mainline
FLEET SERVICE

Auto[®]
Value
Parts Stores

Please contact your Sales Representative for any questions.